

Application No. 10/024,232

IN THE CLAIMS:

Please amend Claims 1-7, as follows:

LISTING OF CURRENT CLAIMS

1. (Currently Amended) A valve configuration of an air pressure steel jar of a paint ball gun, ~~mainly is characterized by~~ comprising a steel jar disposed forwardly with a joint; an axial tube is disposed inside the joint and the steel jar; a communicated state exists between the said axial tube and the joint; one end of the said axial tube is connectively disposed with a valve seat; one end of the said valve seat ~~has the function of~~ is disposed with a valve needle thereby providing the forward and backward rotary movements ~~of a valve needle~~; a through hole is disposed on the valve seat ~~relative to the position of~~ corresponding to the valve needle; the said valve needle is externally operated by a manual wheel ~~to obtain the operation of~~ to enable communicating or tightly closing between the inside and outside of the steel jar ~~and the outside~~.

2. (Currently Amended) A The valve configuration of an air pressure steel jar of a paint ball gun according to Claim 1, a conduct structure

Application No. 10/024,232

prepared for outwardly releasing the pressure is disposed on the ~~said~~ valve needle, via a force conduct hole distanced by a band fuse with pressure resistance slightly smaller than that of a the steel jar.

3. (Currently Amended) ~~A~~ The valve configuration of an air pressure steel jar of a paint ball gun according to Claim 1, wherein the ~~said~~ manual wheel directly links the ~~said~~ valve ~~set~~ needle; a stop leak ring is disposed between the ~~said~~ valve needle and the steel jar.

4. (Currently Amended) ~~A~~ The valve configuration of an air pressure steel jar of a paint ball gun according to Claim 1, wherein ~~the inside of the~~ joint disposed at ~~the~~ a forward end of the steel jar ~~is disposed with having a~~ filter element therein.

5. (Currently Amended) ~~A~~ The valve configuration of an air pressure steel jar of a paint ball gun according to Claim 1, wherein ~~the~~ an outer rim of the joint disposed on the steel jar has threads provided ~~for~~ to enable the locking with ~~the~~ a bore.

6. (Currently Amended) ~~A~~ The valve configuration of an air pressure steel jar of a paint ball gun according to Claim 1, wherein a rubber valve is disposed between the ~~said~~ valve needle and the valve seat.

Application No. 10/024,232

7. (Currently Amended) A valve configuration of an air pressure steel jar of a paint ball gun, ~~comprising the said~~ a valve and ~~the~~ a valve needle is assembled by rotary joint; ~~the~~ a through hole disposed on the valve is situated in ~~the~~ a lateral aspect of the valve needle; wherein the through hole having an aperture size corresponding to the displacement of the valve needle, relative to the aperture size of the through hole, achieves the adjustment of thereby adjusting the pressure thereof.